
# Precise reliability



## **Machining**

#### CNC vertical turning lathe

| Outside diameter | max. | 3200 mm |
|------------------|------|---------|
| Rotating height  | max. | 1200 mm |
| Weight           | max. | 5 to    |

#### **CNC** boring mill

| Length | max. | 3000 mm |
|--------|------|---------|
| Width  | max. | 2000 mm |
| Height | max. | 1400 mm |
| Weight | max. | 5 to    |

#### **CNC** center lathe

| Outside diameter | max. | 800 mm  |
|------------------|------|---------|
| Turning length   | max. | 4000 mm |
| Weight           | max. | 4 to    |

#### **CNC** milling machine

| Length | max. | 1525 mm |
|--------|------|---------|
| Width  | max. | 760 mm  |
| Height | max. | 625 mm  |
| Weight | max. | 3 to    |



## Measuring technology at Stooss

#### Length accuracy

2.8 μ on 450 mm length

### Approx. measuring range

2000 x 3000 x 1200 mm





#### SCHMIEDEWERK STOOSS AG

Maienbrunnenstrasse 8
CH-8908 Hedingen
Telephone +41 43 322 62 00
Fax +41 43 322 62 01
info@stooss.com
www.stooss.com






**Product Program** 

## **Open-Die Forgings**

#### Rectangular bars and plates

| Length | max. | 4000 mm |
|--------|------|---------|
| Width  | max. | 1300 mm |
| Height | max. | 400 mm  |
| Weight | max. | 5 to    |








#### **Shafts**

| Length   | max. | 4000 mm |
|----------|------|---------|
| Diameter | max. | 500 mm  |
| Weight   | max. | 3 to    |



#### Rounds blanks, Hubs, solid or punched hole


| Height   | max. | 400 mm  |
|----------|------|---------|
| Diameter | max. | 1500 mm |
| Weight   | max. | 5 to    |






#### Shafts, flanged shafts, rotors etc.

| Length   | max. | 4000 mm |
|----------|------|---------|
| Diameter | max. | 1000 mm |
| Weight   | max. | 3 to    |



#### Sleeves

| Outside diameter | max. | 1300 mm |
|------------------|------|---------|
| Inside diameter  | min. | 200 mm  |
| Height           | max. | 900 mm  |
| Weight           | max. | 5 to    |





| Length   | max. | 4000 mm |
|----------|------|---------|
| Diameter | max. | 1000 mm |
| Weight   | max. | 3 to    |



## Forged parts from Stooss are out-

Stooss forging technology

gives shape to steel...

...and offers its customers exceptional advantages:

- material selected on the strength of its analysis and degree of purity
- exact shaping

standing because of:


- ideal degree of forming
- optimum grain structure
- minimum allowances
- narrow tolerances

- thermal treatment relevant to the application
- excellent manufacture in terms of surface quality and accuracy of form
- most suitable for processing on CNC machines
- reduction of mechanical processing time thus saving costs
- high degree of security against fatigue cracks

## Seamless Hot Rolled Forgings

#### Rings in rectangular shape


| Outside diameter | max. | 3700 mm      |
|------------------|------|--------------|
| Inside diameter  | acc  | . to request |
| Height           | max. | 700 mm       |
| Weight           | max. | 5 to         |
|                  |      |              |





#### **Profiled rings**

| max. | 3000 mm      |
|------|--------------|
| acc. | to request   |
| max. | 600 mm       |
| max. | 5 to         |
|      | acc.<br>max. |





#### Balls

| Outside diameter | max.            | 920 mm |
|------------------|-----------------|--------|
| Inside diameter  | acc. to request |        |
| Height           | max.            | 700 mm |
| Weight           | max.            | 1.7 to |

